

# B R A I T H

## Manufacturing dimensions

	100mm Dia	88mm Dia	76mm Dia	63mm Dia	50mm Dia
<b>Pipe</b>					
Internal diameter	100	85	76	60	50
External diameter	114	100	88	76	63
Thickness	6	6	6	6	6
Diameter over spigot bead	104	111	98	85	69
<b>Socket</b>					
Internal diameter	127	114	100	88	73
External diameter	136	130	117	104	88
Thickness	6	6	6	6	6
Internal depth	76	76	69	69	63
External diameter over socket beads	133	146	139	114	100
Caulking clearance	6	6	3	3	3
<b>Ears</b>					
Length of flange overall	212	193	177	161	146
Centre to centre of holes	180	161	146	130	114

## Loose Couplings

Code Ref	L20/SOC	L25/SOC	L30/SOC	L35/SOC	L40/SOC
Pipe Dia mm	50	63	75	87	100
a	45	45	38	38	35
b	95	95	90	86	80



## Slip Couplings

Code Ref	L20/SOC/S	L25/SOC/S	L30/SOC/S	L35/SOC/S	L40/SOC/S
Pipe Dia mm	50	63	75	87	100
a	95	95	89	95	79



## Blank End

Code Ref	L30/BE	L35/BE	L40/BE
Pipe Dia mm	75	87	100
a	76	76	70



## Socket Reducer

Code Ref	L30/SR/20	L40/SR/20	L40/SR/30
Pipe Dia mm	75	100	100
a	51	76	51
b	76	76	70

